

Pera



HORIZONTAL DESTEMMER

H 600 - H 800 - H 1000

To contact us
click here 

THE SIGNATURE OF QUALITY MATERIALS

Rue de la Métallurgie - 34510 Florensac - FRANCE - (33) 04 67 77 01 21 - Fax (33) 04 67 77 00 44 - e.mail : pera@pera.fr



HORIZONTAL DESTEMMER

H 600 - H 800 - H 1000

GENERALITIES

Our experience and ongoing research has led to the design of the new PERA H 600, H 800 and H 1000 destemmers. Our aim is always to concentrate on making winemaking machines, and to make the engineering fit the task. In the new H series destemmers we provide improved œnological quality of the derived product, and the reliability that is consistent with such an important winery machine.

The result of our responses to suit the wine-making demands is a range of machines that satisfy the need for improved œnologi-

cal requirements and are reliable, easy to clean and service. All the principal components are made of stainless steel, and drive systems are as direct as possible to remove the need for chains and sprockets.

CHARACTERISTICS

Improvements in product flow and quality are achieved by :

- A large diameter cage that allows free movement of the grapes, and rotates independently of the separator shaft. The cage is fabricated from two segments of stamped screen, with different hole sizes in each segment.

- The grape separator shaft has strong, pipe fingers that finish with directable stainless steel paddles. The speed of rotation of this part is electronically controlled.

MAINTENANCE

Cleaning and maintenance are facilitated by :

- Easy access due to full length covers.
- Direct drive system connection
- One hand lifting of the drive system
- Direct access to the cage and shaft for removal or interchanging

LÉGENDE DES ÉQUIPEMENTS

- 1 Independent cage drive
- 2 Electronic speed control on separator shaft
- 3 Stainless steel cage drive sprocket
- 4 Integral opening cover
- 5 CIP header with spray jets
- 6 Directable paddles on the separator shaft
- 7 Stamped holes in the stainless steel cage
- 8 "Tilt up", integral motor support frame
- 9 PVC flap, seals the stalk discharge
- 10 Support struts
- 11 Stainless steel cage support rollers
- 12 Stalk discharge chute



CHARACTERISTICS

| | Weight net (Kg) | Rate per hour | Installed capacity (Kw) |
|-----------------------------|-----------------|---------------|-------------------------|
| Horizontal destemmer H 600 | 500 | 30 | 4,1 |
| Horizontal destemmer H 800 | 1000 | 50 | 5,5 |
| Horizontal destemmer H 1000 | 1200 | 70 | 7 |

Les caractéristiques sont données à titre indicatif et peuvent être modifiées sans préavis du constructeur.

To contact us
click here 

THE SIGNATURE OF QUALITY MATERIALS

Rue de la Métallurgie - 34510 Florensac - FRANCE - (33) 04 67 77 01 21 - Fax (33) 04 67 77 00 44 - e.mail : pera@pera.fr

